



Accessory boxes and enclosures

Square and rectangular dry lining accessory boxes



Circular dry lining accessory boxes



Moulded enclosures Adaptable boxes

Adaptable boxes as supplied, have a degree of IP66 protection. Any openings that are drilled or cut into the box body and are not sealed with appropriate IP66 components, or a failure to use the silicon rubber seal fitted will negate the IP66 rating.

Lug Colour	Adjustment
Grey	1 – 9mm
White	6 – 14mm
Green	18 – 25mm
Black	9 – 26mm

Lug Colour	Type
White	Dual entry box

Note: Ceiling mounted circular boxes can support 3kg centrally at 60°C maximum subject to ceiling construction.

Cut out dimensions

Box type	Cut out size
1 gang	73 x 73mm
2 gang	135 x 73mm
Dual gang	157 x 73mm

	Dual entry
Board thickness	9-32mm
Entry	Ø20mm x2 off KO
Aperture size	Ø70.0mm
Internal depth	34mm
Fixing centres	M4.0 x 50.8mm M3.5 x 60.3mm

Screening

- Boxes available with copper spray screening to protect data outlets from electromagnetic interference.

Part M boxes and box assemblies

- Comply with the requirements of Part M (DDA)
- Odyssey coloured boxes (DD1510 and DD1520) with coloured flanges to contrast with trunking cover colour.
- ESPM box assemblies with contrasting coloured flush accessory box frames. For colour varieties please view the perimeter trunking pages.

Adjustable accessory box depth by product range

	Maximum adjustment range	Page Reference
PowerPoles and PowerPosts		
Series 1 and 2	32 - 40mm	186
PVC-U Perimeter Trunking		
Mono 10	32 - 40mm	55
Mono Plus 20	32 - 40mm	57
Compact 1	32 - 40mm	59
Compact 2	32 - 40mm	61
Compact 3	32 - 40mm	63
Twin165	32 - 47mm	66
Sterling Profile 1 - 3	32 - 45mm	68
Sterling Profile 4*	32 - 45mm	74
Sterling Curve	32 - 45mm	77
Odyssey	32 - 40mm	84
Twin Plus	32 - 47mm	86
XL Trunking 201 - 202	32 - 47mm	89
XL Trunking 211 - 212	32 - 47mm	93
PVC-U Trunking		
Bench Trunking	32 - 47mm	115
Aluminium Trunking		
Bench Trunking	32 - 47mm	152
Elegance 110	32 - 40mm	154
Sterling Profile 1 - 3	32 - 40mm	156
Sterling Curve Profile 1 & 2	32 - 40mm	160
Elegance 170	32 - 40mm	165
Twin Plus	32 - 47mm	167
XL Trunking 301 - 302	32 - 47mm	170

*The EAB1/2 can be adjusted to 45mm in the main compartment only. Where the EBE1 Base Extension is used the maximum adjustment achievable is 40mm