

## Bendex Loblite Product Data Sheet

Product Range	LOBSGSKTWH, LOBSGSKTLG	<p>Image for reference only</p> 
Description	Single Gang IP66 Socket	
Key Features	IP66 Rated 13A integral socket Unswitched	
Dimensions	109 x 75 x 90mm	
Material(s)	Polycarbonate Colour: White or Light Grey	
Compliance / Standards(s)	<p>CE &amp; UKCA Marked</p> <p>Low Voltage Directive 2014/35/EU</p> <p>The Electrical Equipment (Safety) Regulations 2016</p> <p>BS 7671:2018</p> <p>BS EN 60529:1992+A2:2013</p> <p>BS 1363-2:1995+A4:2012</p> <p>BS 1363-4:1995+A4:2012</p> <p>BS EN 60669-1:1999+A2:2008</p> <p>EMC Emissions - EN 55014-1:2006 &amp; EN 55014-1:2000 inc A1:2001 &amp; A2:2002</p> <p>EMC Immunity - EN 61543:1995 inc A11:2003, A12:2005 &amp; A2:2006</p> <p>Nemko Ltd, Certificate C11/42811 – BS EN 60529:1992 (Amd. 1 and 2) IP66</p> <p>Nemko Ltd, Certificate C11/42713 – BS 1363-2:1995 (Amd. 1 to 3) Socket Stone</p>	
Packaging	Recyclable	

### Sustainability

In-screed Adaptors are made from Polycarbonate, a material that is 100% recyclable