

55-65 Castleham Road, St Leonards on Sea

East Sussex, TN38 9NU

Customer Services: +44 (0) 1424 856600


T: +44 (0) 1424 856655

E: sales@marshall-tufflex.com

www.marshall-tufflex.com

Bendex Heavy Gauge Conduit Product Data Sheet

| Product Range | HG20, HG25 & HG32 | Image f | |
|------------------------------|--|----------------------|--|
| Description | PVCu Round Conduit | | |
| Key Features | Heavy Gauge Range of Inspection Elbows, Bends & Tees Range of fittings Range of Round & Square boxes Operating Temperature -5°C to +60°C Non-Flame Propagating to BS EN 61386-1 High Impact Resistance to -5°C Heavy Gauge Requirements of BS EN 61386-1 | | |
| Dimensions | Refer to Table | | |
| Material(s) | PVCu (White and Black) - HG32 White only | Product Code | |
| Compliance / Standards(s) | CE & UKCA Marked Low Voltage Directive 2014/35/EU The Electrical Equipment (Safety) Regulations 2016 BS 7671:2018 BS EN 61386-1:2008+A1:2019 BS EN 61386-21:2021+A11;2021 BS 4607-1:1984+A2:2010 BS 4607-5:1982+A3:2010 BS EN 60695-2-11:2021 | HG20 HG25 HG32 | |
| Packaging | Recyclable | | |



| Product Code | Nominal | Minimum |
|-----------------|----------|----------|
| | Outside | Inside |
| | Diameter | Diameter |
| HG20 | 20.0mm | 16.3mm |
| HG25 | 25.0mm | 20.6mm |
| HG32 | 32.0mm | 26.4mm |



We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

Our white extruded Conduit and Channel PVC-U products are manufactured from a minimum of 80% recycled material and up to 100% recycled content, depending on material availability.

This range is manufactured from PVC-U, a material that is 100% recyclable, is flame retardant and self-extinguishing.

Deama



