


Channelling Product Data Sheet

Product Range	CH13WH, CH25WH & CH38WH	<p>Image for reference only</p> 
Description	PVCu Channel	
Key Features	<p>For protecting channelled electrical wiring routes. Constructed from robust, heavy gauge material. Can be cut to required length Operating Temperature -5°C to +60°C Non-Flame Propagating to BS EN 61386-1 High Impact Resistance to -5°C Heavy Gauge Requirements of BS EN 61386-1</p>	
Dimensions	<p>CH13WH - 13mm x 8mm x 2m CH25WH - 25mm x 8mm x 2m CH38WH - 38mm x 9mm x 2m</p>	
Material(s)	PVCu (White)	
Compliance / Standards(s)	<p>CE & UKCA Marked Low Voltage Directive 2014/35/EU The Electrical Equipment (Safety) Regulations 2016 BS 7671:2018 BS EN 61386-1:2008+A1:2019 BS 4607-1:1984+A2:2010</p>	
Packaging	Recyclable	

Sustainability



We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

Our white extruded Conduit and Channel PVC-U products are manufactured from a minimum of 80% recycled material and up to 100% recycled content, depending on material availability.

This range is manufactured from PVC-U, a material that is 100% recyclable, is flame retardant and self-extinguishing.