


Basor 100mm Metal Ladder Product Data Sheet

Product Range	Metal Cable Management Systems	<p>Image for reference only</p>  <p>Impact Strength 20J (IK10) Operating temperature -50°C to +150°C</p>
Description	Ladder 100mm high – 1.5mm gauge	
Key Features	<ul style="list-style-type: none"> Greater load capacity due to rail design Safety edge that provides increased strength and protection for installers. Strut type rungs 41x21mm Perforated side panel Full range of fittings Compatible with and fixable to our ranges of metal strut and suspension systems. 	
Dimensions	Height 100mm with widths of 150, 300, 450, 600, 750 & 900mm	
Material(s)	Hot Dipped Zinc Coated Low Carbon Steel	
Compliance / Standards(s)	CE & UKCA Marked Low Voltage Directive 2014/35/EU The Electrical Equipment (Safety) Regulations 2016 EN 61537 EN 50085 UL certifide	
Packaging	Recyclable	

	Support Spacing (m)					
	2	2.5	3	4	5	6
	Safe Working Load (kg/m)					
H75x1.5	260	167	116			
H100x1.5	468	300	208	117	75	
H125x2.0		524	364	205	131	91
H150x2.0			472	265	170	118
H200x2.0			725	408	261	181

Note: For Support spans wider the 3 metres ask for wide span special union joints.