




## XL201 Product Data Sheet

Product Range	PVC-U Perimeter Trunking Systems	<p>Image for reference only</p> 
Description	XL 201	
Key Features	<ul style="list-style-type: none"> <li>3 segregated compartments</li> <li>Suitable for Dado and Skirting applications</li> <li>Tamper Proof Covers</li> <li>Flush Fitting Accessories</li> <li>CAT 6 Compliant</li> <li>Part M Boxes</li> <li>Impact (Lengths) - IK08 (5 Joules)</li> <li>Impact (Fittings) - IK08 (5 Joules)</li> </ul>	
Dimensions	220mm x 65mm Profile	
Material(s)	PVCu	
Compliance / Standards(s)	<ul style="list-style-type: none"> <li>CE &amp; UKCA Marked</li> <li>Low Voltage Directive 2014/35/EU</li> <li>The Electrical Equipment (Safety) Regulations 2016</li> <li>BS 7671:2018</li> <li>BS EN 50085-1:2005+A1:2013</li> <li>BS EN 50085-2-1:2006+A1:2011</li> <li>BS 5733:2010+A1:2014</li> <li>BS EN IEC 60695-2-11:2021</li> </ul>	
Packaging	Recyclable	

### Sustainability



We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

Our extruded PVC-U products are manufactured from combination of recycled PVC-U and virgin PVC-U with some base products produced from 100% recycled material.

This range is manufactured from PVC-U, a material that is 100% recyclable, is flame retardant and self-extinguishing.