




Twin Plus PVCu Product Data Sheet

Product Range	PVC-U Perimeter Trunking Systems	<p>Image for reference only</p> 
Description	TwinPlus PVCu	
Key Features	<p>2 large, segregated compartments</p> <p>Suitable for Dado and Skirting applications</p> <p>Tamper Proof Covers</p> <p>Flush Fitting Accessories</p> <p>Up to CAT 7a Compliant</p> <p>Part M Boxes</p> <p>Impact (Lengths) – IK08 (5 Joules)</p> <p>Impact (Fittings) – IK06 (1 Joules)</p>	
Dimensions	210mm x 57mm Profile	
Material(s)	PVCu	
Compliance / Standards(s)	<p>CE & UKCA Marked</p> <p>Low Voltage Directive 2014/35/EU</p> <p>The Electrical Equipment (Safety) Regulations 2016</p> <p>BS 7671:2018</p> <p>BS EN 50085-1:2005+A1:2013</p> <p>BS EN 50085-2-1:2006+A1:2011</p> <p>BS 5733:2010+A1:2014</p> <p>BS EN IEC 60695-2-11:2021</p>	
Packaging	Recyclable	

Marshall-Tufflex Cable Management systems are suitable for a variety of data category cables. The information in the table below is based on average data cable diameters from a range of cable manufacturers.

In all cases it is recommended to contact the data cable manufacturer to confirm the specification, and minimum bend radius of the data cable prior to installation.

Data Cable	Un-Shielded	Shielded
CAT5	Up to 10 x Cable Diameter	-
CAT5e	Up to 10 x Cable Diameter	Up to 7 x Cable Diameter
CAT6	Up to 8 x Cable Diameter	Up to 7 x Cable Diameter
CAT6a	Up to 8 x Cable Diameter	Up to 6 x Cable Diameter
CAT7	-	Up to 6 x Cable Diameter
CAT7a	-	Up to 6 x Cable Diameter

REASSURINGLY RECYCLED

We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

Our extruded PVC-U products are manufactured from combination of recycled PVC-U and virgin PVC-U with some base products produced from 100% recycled material.

This range is manufactured from PVC-U, a material that is 100% recyclable, is flame retardant and self-extinguishing.