


Sterling Curve Aluminium Product Data Sheet

Product Range	Aluminium Trunking	<p>Image for reference only</p> 
Description	Sterling Curve Profiles 1	
Key Features	<ul style="list-style-type: none"> 3 segregated compartments Suitable for Dado applications Tamper proof single piece cover Flush Fitting Accessories Up to CAT 7a Compliant Compatible with MT flush power and data and standard UK wiring accessories First Class EMC/EMI screening performance Part M compliant Flame Retardancy for Polycarbonate Fittings UL94 V0 @ 1.5mm Impact (Lengths) – IK10 (20 Joules) Impact (Fittings) – IK07 (2 Joules) 	
Dimensions	167mm x 50mm Profile	
Material(s)	Aluminium and Polycarbonate (Moulded Fittings)	
Compliance / Standards(s)	<ul style="list-style-type: none"> CE & UKCA Marked Low Voltage Directive 2014/35/EU The Electrical Equipment (Safety) Regulations 2016 BS 7671:2018 BS EN 50085-1:2005+A1:2013 BS EN 50085-2-1:2006+A1:2011 BS 5733:2010+A1:2014 	
Packaging	Recyclable	

Sustainability
Curve Sterling Trunking is manufactured from Aluminium, a material that is 100% recyclable