


Sterling Curve Aluminium Product Data Sheet

Product Range	Aluminium Trunking	<p>Image for reference only</p> 
Description	Sterling Curve Profile 2	
Key Features	<p>3 segregated compartments</p> <p>Suitable for Dado and Skirting applications</p> <p>Tamper proof single piece cover</p> <p>Flush Fitting Accessories</p> <p>Up to CAT 7a Compliant</p> <p>Compatible with MT flush power and data and standard UK wiring accessories</p> <p>First Class EMC/EMI screening performance</p> <p>Part M compliant</p> <p>Flame Retardancy for Polycarbonate Fittings UL94 V0 @ 1.5mm</p> <p>Impact (Lengths) – IK10 (20 Joules)</p> <p>Impact (Fittings) – IK07 (2 Joules)</p>	
Dimensions	167mm x 50mm Profile	
Material(s)	Aluminium and Polycarbonate (Moulded Fittings)	
Compliance / Standards(s)	<p>CE & UKCA Marked</p> <p>Low Voltage Directive 2014/35/EU</p> <p>The Electrical Equipment (Safety) Regulations 2016</p> <p>BS 7671:2018</p> <p>BS EN 50085-1:2005+A1:2013</p> <p>BS EN 50085-2-1:2006+A1:2011</p> <p>BS 5733:2010+A1:2014</p>	
Packaging	Recyclable	

Sustainability

Curve Sterling Trunking is manufactured from Aluminium, a material that is 100% recyclable